

# PRODUCT DATA SHEET

## SERVO PREMIUM XHP 15W-40



### DESCRIPTION

Servo Premium XHP 15W-40 is high performance diesel engine oil, which provides excellent protection against corrosive wear in all types of diesel engines. This oil is suitable for all seasons and retains high level of alkalinity during use.

### APPLICATION

Servo Premium XHP 15W-40 is recommended for:

- Naturally aspirated and turbocharged diesel engines
- Also recommended for Stationary DG Sets operating on Distillate fuels.

### PERFORMANCE BENEFITS

Servo Premium XHP 15W-40 provides:

- Improved cold starting and faster engine warm up.
- Outstanding engine cleanliness even under most severe operating conditions.
- Exceptional thermal and oxidation stability to resist decomposition in super charged engines operating with high ring zone temperatures.
- Longer battery life.
- Lower fuel and engine oil consumption.

### PERFORMANCE STANDARDS

Servo Premium XHP 15W-40 meets the following specifications.

☞ API CE

### CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity cSt @ 100°C	14.0 – 15.0
Viscosity Index, Min.	135
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 24
TBN mg KOH/gm	10 – 12

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) OR [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

May-20