

# PRODUCT DATA SHEET

## SERVO XEE SJ 15W-40



### DESCRIPTION

Servo XEE SJ 15W-40 is a long life, high performance engine oil for new generation petrol vehicles. This oil is blended from high viscosity index base stocks and contain additives to meet the highest quality performance standard

### APPLICATION

Servo XEE SJ 15W-40 is recommended for new generation passenger cars using petrol.

### PERFORMANCE BENEFITS

- ☞ Superior performance in terms of improved oil and engine life.
- ☞ Less oil thickening, better deposit control.
- ☞ Fuel savings and low oil top up.
- ☞ Catalytic Convertor Compatible.

### PERFORMANCE STANDARDS

- ☞ API SJ, SAE 15W-40

### APPROVAL

- ☆ Tata Motors for using in Nano Cars.

### CHARACTERISTICS

SAE GRADE	15W-40
Kin. Viscosity @ 100°C, cSt	13.5 - 15.5
Viscosity Index, Min	135
Flash Point, COC, °C, Min	200
Pour Point, °C, Min.	(-) 24
TBN, mg KOH/gm	5.80 – 7.50

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) **OR** [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

May-20