

DESCRIPTION

Servocyl M oils are highly refined steam cylinder lubricants having excellent thermal and chemical stability. These oils provide good resistance to the washing effect of moisture and separate easily from exhaust steam and condensate.

Servocyl M oils are non-additive treated mineral oils, blended from high quality, specially refined, high viscosity index base stocks.

APPLICATION

Servocyl M oils are recommended for cylinder lubrication of steam engines handling superheated steam. These oils are specially suitable for services demanding straight mineral oil where –in ready separation of condensate from lubricant is necessary so that the condensate can be further used in certain process work.

These oils are not recommended for wet steam conditions.

PERFORMANCE BENEFITS

Servocyl M oils

- Enable higher loading of equipment, since they have high-load carrying ability
- Minimise wear of cylinder wall and piston rings
- Protect engine parts against rusting and corrosion
- Reduce steam consumption, due to excellent sealing characteristics and low frictional losses
- Minimise tendency of deposit

PERFORMANCE STANDARDS

Servocyl M 1000 meets the following specification :

- IS : 1589-1960 with amendment No. 1 of 1966 for Cylinder Oil Grade 2, Type 1 with minor deviation in flash point requirement

CHARACTERISTICS

ISO VG	680	1000	1500
Kinematic Viscosity, cSt @ 40°C	640-680	980-1050	1450-1550
Viscosity Index, Min.	85	80	80
Flash Point (COC), °C Min.	280	280	280
Pour Point, °C Max.	6	6	6
CCR, % Wt., Max.	3.5	3.5	4.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20