

DESCRIPTION

Servocress 68 is new generation synthetic LPG compressor oil formulated with high performance base stocks (Polyalkylene Glycols) and additive technologies. This oil is tailor made to provide superior thermal and oxidation stability over a wide range of temperatures, reduced volatility and protection against corrosion.

APPLICATION

Servocress 68 is an excellent synthetic compressor oil for lubrication of LPG compressors providing desired viscosity at operating temperature. However, Servocress 68 is recommended for Rotary Screw Compressors, Vane Compressors and cylinder lubrication of Reciprocating compressors. This grade is an excellent choice when extended drain intervals are desired.

PERFORMANCE BENEFITS

- Multi fold increase in oil service life.
- Improved lubricity.
- Excellent Low / High temperature operability.
- Reduced volatility
- Enhanced oxidation stability
- Reduced carbon forming tendency
- Increased resistance to oil thickening and acidity build up.
- Substantial savings in operating cost.

CHARACTERISTICS

ISO VG	68
Colour	1.0
Kinematic Viscosity cSt @ 40°C	64 – 74
Viscosity Index, Min	210
Pour Point, °C, Max	(-)36
Flash Point, COC, °C, Min	215
Water solubility	Soluble

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20