PRODUCT DATA SHEET SERVO PREMIUM (N) 15W-40

DESCRIPTION

Servo Premium (N) 15W-40 is **API certified**, premium commercial multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of new generation diesel engines for on and off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Catalytic Converter compatible.

CHARACTERISTICS

SAE GRADE 15W-40 Kinematic Viscosity, cSt @ 100°C 13.5 - 15.5 Viscosity Index, Min. 130 TBN, mg KOH/g 9.5 - 11.5 Flash Point, (COC)°C, Min. 200 Pour Point °C, Max. (-) 24

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051 **E-Mail:** tservices@indianoil.co.in **OR** tech services@indianoil.co.in

APPLICATION

Servo Premium (N) 15W-40 is recommended for new generation commercial diesel vehicles of both American and European design such as Caterpillar and Cummins operating on Heavy duty on-highway and off-highway equipments.

PERFORMANCE STANDARDS

- * API CH-4
- * MB 228.3
- * ACEA E3-96

APPROVAL

* M/s MTU, Germany for the oil category 2 for the application in MTU engines & DDC engines series 2000 & 4000.