PRODUCT DATA SHEET SERVOSYNTH SJ 5W-40



DESCRIPTION

Servosynth SJ oil is a semi-synthetic superior performance engine oil recommended for new generation passenger cars and light duty diesel vehicles.

APPLICATION

Servosynth SJ oil is recommended for new generation imported and Indian passenger cars using petrol and light duty diesel vehicles operating under widely varying ambient conditions.

PERFORMANCE BENEFITS

- Superior wear protection.
- Superior deposit control.
- Extended component life.
- Excellent engine cleanliness.
- Lower oil consumption
- Better Fuel Economy
- Catalytic Convertor Compatible

PERFORMANCE STANDARDS

- API SJ for Petrol and API CF in diesel service.
- Meets ACEA A3/B3 98, MB 229.1

CHARACTERISTICS

SAE GRADE	5W-40
Kin. Viscosity @ 100°C, cSt	13.0 – 14.0
Viscosity Index, Min	150
Flash Point, COC, °C, Min	200
Pour Point, °C, Min.	(-) 51
TBN, mg KOH/gm	9 – 11

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051 May-20

E-Mail: servotechserv@indianoil.in OR servots@indianoil.in