

# PRODUCT DATA SHEET

## SERVOFRIZ S



### DESCRIPTION

Servofriz S Oils are premium Lubricants formulated for the lubrication of reciprocating and rotary refrigeration compressors.

### APPLICATION

Servofriz S Oils are recommended for the lubrication of a wide range of refrigeration compressors.

These oils can be used with all fluorocarbon refrigerant and with hydrocarbons and ammonia in refrigeration and air conditioning applications where evaporator temperatures are lower than the pour point of the oil.

### PERFORMANCE BENEFITS

- Long Service Life
- Keeps Compressor Parts clean
- High Fluidity at Low temperatures
- Reduce Maintenance of parts

### CHARACTERISTICS

ISO VG	SERVOFRIZ S				
	22	32	46	57	68
Kin. Viscosity @ 100°C, cSt	20-24	29-35	43-45	54-60	63-70
Flash Point, COC, °C, Min	144	154	160	164	170
Pour Point, °C, Max	(-) 45	(-) 30	(-) 27	(-) 24	(-) 24

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in