

DESCRIPTION

Servosystem HLP oils are high performance hydraulic oils having high FZG rating. These oils provide superior antiwear protection, excellent oxidation and thermal stability, outstanding hydraulic stability and good demulsibility. Servosystem HLP oils also possess superior filterability characteristics. These oils provide problem free service and have been found to be far superior in performance compared to other commercially available anti-wear, heavy duty hydraulic oils.

APPLICATION

Servosystem HLP oils are recommended as a fluid media in hydraulic systems, operating under extremely severe conditions. These oils are recommended for sophisticated high performance electro-hydraulic or numerically controlled systems. Servosystem HLP oils are also recommended for lubrication of screw compressors requiring oil of excellent thermal stability and low CCR value. These oils are not suitable where the components are of silver or silver coated.

PERFORMANCE BENEFITS

Servosystem HLP oils

- # ensure long service life due to outstanding oxidation and thermal stability.
- # provide sludge free high temperature performance.
- # provide excellent filterability characteristics.
- # readily separate from water because of excellent demulsibility characteristics.
- # provide superior long term protection against rust and corrosion.
- # Ensure overall problem free performance.

PERFORMANCE STANDARDS

Servosystem HLP oils are formulated to meet the following specifications :

- # Cincinnati Milacron P-69
- # DIN 51524 Part 2
- # DENISON HF-O
- # US STEEL 127
- # IS : 11656-1986 (Reaffirmed 1991)
- # IS:10522-1983(Reaffirmed 1993)
- # ATLAS COPCO R8 & R9, HOESCH HLP

Servosystem HLP oils are recommended by the leading equipment manufacturers such as :

- # Atlas Copco (India) Ltd.

CHARACTERISTICS

ISO VG GRADE	15	22	32	46	68	100	150
Kin. Viscosity @ 40°C, cSt	14.2 – 15.8	20-24	29-33	43-48	64-72	96-104	145 – 155
Viscosity Index, Min	100	100	100	98	95	95	90
Flash Point(COC), °C, Min	170	165	200	204	210	210	230
Pour Point, °C, Max	(-) 30	(-)21	(-)21	(-)15	(-)12	(-)12	(-)6
Emulsion Test D-1401, 40-37-3, Minutes, Max	15	15	15	15	15	20	20
FZG, Rating Stage, Failure	-	-	10	10	10	10	11

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20