PRODUCT DATA SHEET SERVO BOAT POWER PLUS



DESCRIPTION

Servo Boat Power Plus is low smoke semisynthetic two stroke engine oil developed to meet the critical requirements of high performance water cooled two stroke engines manufactured by leading engine makers. It is blended from selected base stocks and additives to minimise spark plug fouling and preignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It contains a diluent for easy mixing with gasoline.

PERFORMANCE BENEFITS

- Low exhaust smoke
- Maintains engine cleanliness
- Minimizes spark plug fouling
- Reduces port deposits and ring sticking
- Prevents seizure and scuffing
- Is easily pumpable by oil injection system

APPLICATION

Servo Boat Power Plus is recommended for lubrication of outboard motors operating on two stroke engines.

PERFORMANCE STANDARDS

Meets

NMMA TC-W3 specifications.

CHARACTERISTICS

Appearance	Clear
Kinematic Viscosity @ 40°C, cSt	42-60
Flash Point (PMCC), °C, Min	90
Pour Point, °C, Max	(-) 30
Sulphated ash % wt., Max	0.05

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in OR servots@indianoil.in

May-20