SERVO FUTURA D



DESCRIPTION

Servo Futura D oil is a long life, high performance diesel engine oil compatible for engines conforming to advance emission norms. This oil is highly refined high viscosity index base stocks and contain additives to meet the highest performance standard for Diesel Engines.

APPLICATION

Servo Futura D oil is recommended for new generation diesel vehicles confirming to advanced emission norms. This oil is also recommended for new generation petrol vehicles.

PERFORMANCE BENEFITS

- Increased component life.
- Lower maintenance costs.
- Excellent Engine Cleanliness.
- Excellent control on soot induced oil thickening.
- Outstanding control on oil consumption.
- Ensures outstanding protection from wear, high temperature deposits, oil degradation and corrosion.
- Suitable for vehicles fitted with EGR

PERFORMANCE STANDARDS

- Meets API CI-4 requirement for diesel engine and API SL requirement for petrol engine.
- Meets MB 228.3 and Volvo VDS3 and Cummins CES 20076/20077/20078 ACEA E7 requirement.

CHARACTERISTICS

SAE GRADE	15W-40
Kin. Viscosity @ 100°C, cSt	14 - 15
Viscosity Index, Min	135
Flash Point, COC, °C, Min	200
Pour Point, °C, Min.	(-) 24
TBN, mg KOH/gm	9 – 12.5
Sulphated Ash % wt	1.23 – 1.64

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tservices@indianoil.co.in OR tech services@indianoil.co.in