

PRODUCT DATA SHEET

SERVO TRANSTRAC HVI



DESCRIPTION

Servo Transtrac HVI is a mineral oil based hydraulic brake fluid which ensures long service life of the hydraulic control brakes and clutches of HEMM. It remains clear and uniform fluid under extreme cold climatic conditions, enabling satisfactory operation of brake systems. It also lubricates the moving parts of the brake system very effectively.

APPLICATION

Servo Transtrac HVI is designed for use in hydraulic control brakes and clutches of L&T – Case make equipments. The high viscosity index enables to get the steady hydraulic output irrespective of wide fluctuation of temperature. The product is having a very low pour point which ensures fluidity at very cold climatic conditions.

PERFORMANCE BENEFITS

Servo Transtrac HVI

- Provides very high safety factor during operation under heavy load
- Provides excellent protection against corrosion to iron, non-ferrous metals and zinc alloys
- Has longer service life, due to excellent oxidation stability

PERFORMANCE STANDARDS

Servo Transtrac HVI meets the requirement of Hydraulic Brakes and Tractor clutches of L&T case as per ISO : 7308 specification.

MANUFACTURERS APPROVAL

Approved by M/s. L&T case for use in Hydraulic control brakes and clutches of L&T - Case make HEMM.

CHARACTERISTICS

Appearance	Clear
Boiling Point, °C Min.	235 Min
Kinematic Viscosity, cSt @ 40 °C, Max. @ 100 °C, Min.	19 - 23 6.0 Min
Viscosity Index	244
Pour Point, Deg C	(-) 58 Max
Flash Point, COC, Deg C	170 Min
TAN, mg KOH/gm	0.20 Max

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20