

DESCRIPTION

Servo Pride GEO oils are high performance medium ash gas engine oils, formulated from high quality mineral oil and select additive system to provide excellent thermal stability and resistance to oxidation and nitration.

APPLICATION

Servo Pride GEO oils are recommended for heavy duty commercial vehicles operating on gaseous fuels like CNG, LPG etc.

PERFORMANCE BENEFITS

- Excellent resistance to oxidation and nitration.
- Excellent resistance to corrosion.
- Ensures engine cleanliness.
- Extra protection for valve guide seats against wear.
- Reduced carbon and sludge formation.

PERFORMANCE STANDARDS

Servo Pride GEO 15W-40 meets the following specifications.

- ✘ CES 20074 of Cummins USA
- ✘ API CF

MANUFACTURERS APPROVAL

- Approved by Swaraj Mazda

CHARACTERISTICS

SAE GRADE	15W-40	20W-50
Kinematic Viscosity cSt @ 100°C	13.5 – 15.5	17.5 – 19.5
Viscosity Index, Min.	130	130
Flash point (COC), °C Min.	200	200
Pour Point, °C Max.	(-) 21	(-) 21
TBN mg KOH/gm	4.5-5.5	4.5-5.5
Sulphated Ash % wt	0.5 – 0.6	0.5 – 0.6

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in