PRODUCT DATA SHEET

SERVO PRIDE SUPREME

DESCRIPTION

Servo Pride Supreme is **API certified**, premium commercial multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of new generation diesel engines for on and off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Has the potential to doubled the oil drain intervals compared to current diesel engine oils.

APPLICATION

Servo Pride Supreme is recommended for new generation commercial diesel vehicles of both American and European design such as Caterpillar and Cummins operating on Heavy duty on-highway and off-highway equipments. It is tailored to the lubrication requirements of engines complying to EURO III. It is especially compounded for use with diesel fuel ranging in sulphur content upto 0.5% by wt.

PERFORMANCE STANDARDS

- API CI-4 / CF/ SL
- MB 229.1
- MB 228.3
- ACEA E-7-08/A3/B3-08/A3/B4-08
- VOLVO VDS-3
- MAN M3275
- MTU Type 2
- MACK EO-M+
- RENAULT RLD 2
- Cummins CES 20076 / 20077 / 20078
- GLOBAL DHD-1
- DEUTZ DQC-III
- CATERPILLAR ECF-1a
- ALLISON C4 LEVEL

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	15.5
Viscosity Index, Min.	135
TBN, mg KOH/g	10.4
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24
CCS @ (-) 20 Deg C	7,000 cP Max

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051
E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in May-20