

PRODUCT DATA SHEET

SERVO INDANE BOAT ENGINE OIL



SERVO®

DESCRIPTION

Servo Indane Boat Engine Oil is blended from highly refined base stocks and balanced additive package containing shear stable VI improver, metallic detergent dispersant and anti-oxidant. This oil is formulated to meet lubrication requirements of LPG operated Marine engines. Servo Indane Boat Engine Oil is red in colour.

APPLICATION

Servo Indane Boat Engine Oil is recommended for

- ☛ Lubrication of LPG operated Marine engines.

PERFORMANCE BENEFITS

Servo Indane Boat Engine Oil

- ☛ Enable easy low temperature starting
- ☛ Minimise fuel and oil consumption
- ☛ Give longer battery life
- ☛ Provide maximum protection to engine parts against rust and corrosion
- ☛ Give good high and low temperature performance in the engine
- ☛ Reduces engine wear.

PERFORMANCE STANDARDS

Meets the following specifications:

API CF/SF
E-DL 2/E-PL 2 of IS:13656-2002
MIL-L-2104 B

CHARACTERISTICS

	Servo Indane Boat Engine Oil
Kinematic Viscosity cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	110
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN, mg, KOH/gm	4.0 – 6.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20