

DESCRIPTION

Servo Calib oils are low viscosity products specially developed as Calibration fluids for Diesel Injection equipments.

APPLICATION

Servo Calib oils are recommended for calibration of Diesel Injectors.

PERFORMANCE BENEFITS

- Increases the life of calibration equipment.
- Excellent seal compatibility
- Excellent oxidation stability property
- Excellent high temperature performance
- Excellent wear protection
- Excellent low temperature characteristics

PERFORMANCE STANDARDS

Servo Calib 2 meets the specification requirement of ISO : 4113.

Servo Calib 5 has been specially developed for Diesel Injector equipments used by Indian Railways.

CHARACTERISTICS

GRADE	Servo Calib 2	Servo Calib 5
Kinematic Viscosity cSt @ 40°C	2.45 – 2.75	5.2 – 6.2
Density, gm/ml @ 29.5 Deg C	0.826	0.835
Pour Point, °C, Max	(-) 10	0
Flash Point, PMCC, °C, Min	75	130

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20