

PRODUCT DATA SHEET

SERVO SPECIAL NG 40



SERVO[®]

DESCRIPTION

Servo Special NG 40 is a Premium Quality ashless gas engine oil, formulated from high quality mineral base oil and select additive system to provide excellent thermal stability and resistance to oxidation and nitration.

APPLICATION

Servo Special NG 40 is recommended for Stationary engines operating on natural gas, CNG, etc.

PERFORMANCE BENEFITS

- ❖ Provides excellent dispersency, detergency
- ❖ Excellent resistance to oxidation and nitration.
- ❖ Excellent resistance to corrosion.
- ❖ Ensures engine cleanliness.
- ❖ Extended component life.
- ❖ Ensures negligible carbon and ash deposit.

PERFORMANCE STANDARDS

- Meets Cooper Bessemer, USA Engineering Standard SE – 114-2

CHARACTERISTICS

| SAE GRADE | 40 |
|---------------------------------|-------------|
| Kinematic Viscosity cSt @ 100°C | 13.5 – 14.0 |
| Viscosity Index, Min. | 90 |
| Flash point (COC), °C Min. | 220 |
| Pour Point, °C Max. | (-) 12 |
| TBN mg KOH/gm | 2.5 |
| Sulphated Ash, %, wt. Max | 0.1 |

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20