

SERVO PREMIUM CF 2 40

DESCRIPTION

Servo Premium CF 2 is high performance low ash Monograde Engine Oil designed to lubricate 2 stroke Detroit Diesel Engines. This grade contain effective balance of select base oils & chemical additives to minimise deposits, wear and scuffing.

APPLICATION

2 Stroke Diesel Engines of Detroit Diesel make, Marine propulsion and power generation, off highway service in Mining, Industrial and Farming application, pick up and delivery service diesel vehicles.

PERFORMANCE BENEFITS

- Enhanced antiwear protection.
- Maintains power output by providing outstanding deposit control.
- Minimise foaming and air entrainment.
- Extended component life.
- Low maintenance cost

PERFORMANCE STANDARDS

- API CF-2 Licensed
- API CD-II
- API CD
- MIL-L-2104D

CHARACTERISTICS

SAE GRADE	40
Kin. Viscosity @ 100°C, cSt	13.0 – 15.0
Flash Point, COC, °C, Min	226
Pour Point, °C, Max	(-) 6
TBN, mg KOH/gm	6.5 – 8.5
Viscosity Index , min	90
Sulphated Ash % wt	0.8 – 1.04

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20