PRODUCT DATA SHEET SERVOFILM 12 PLUS SERVOFILM 12 PLUS



DESCRIPTION

Servofilm 12 Plus is a highly refined water white non-staining pure paraffinic based mineral oil. This product is an excellent ingredient for the manufacture of various rubber products from both natural as well as Synthetic rubber.

APPLICATION

Servofilm 12 Plus is suitable for use as a plasticizer in rubber process industry where there is specific requirement of water-like colour during manufacturing.

PERFORMANCE BENEFITS

Servofilm 12 Plus offer following advantages

- Water-white colour
- High Aniline point
- Low Volatility
- Good compatibility with polar elastomers.
- Rapidly separate from water

CHARACTERISTICS

ISO VG	12
Colour, ASTM, Max	0.5
Kin. Vis. cSt @ 40°C	9 – 13
Viscosity Index, Min	95
Flash Point (COC), °C Min	160
Pour Point, °C Max.	(-)6
TAN, mg KOH/gm, Max	0.05

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051 May-20

E-Mail: servotechserv@indianoil.in OR servots@indianoil.in