

### DESCRIPTION

Servohydrex TH 46 is anti-wear type hydraulic oil having a very high viscosity index and low pour point. This oil is blended with high quality base stocks and is incorporated with oxidation inhibitor and anti-rust additives to give long trouble free service. The defoamant additive prevents build-up of foam in the hydraulic system. Servohydrex TH 46 has special anti-wear additive essential for hydraulic equipment used for heavy duty operations.

### APPLICATION

Servohydrex TH 46 is recommended as fluid media in all hydraulic system where very low operating temperatures are encountered and the application demands use of a very high viscosity index oils.

### PERFORMANCE BENEFITS

- Easy flow at very low temperatures
- Suitable for a wide range of operating temperatures due to its very high viscosity index
- Provide good protection against wear thereby prolonging service life of moving parts
- Possess excellent resistance to oxidation
- Have reduced foaming tendency
- Provide protection against rust and corrosion

### APPROVALS

- Designed to meet the requirement of Tata Hitachi excavators of M/s. TELCON.

### CHARACTERISTICS

ISO VG	46
Kinematic Viscosity, cSt @ 40°C	43-48
Viscosity Index, Min.	135
Flash Point (COC), °C Min.	200
Pour Point, °C Max.	(-) 33
Rust Test, (D-665 B, 24 hrs.)	Pass

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20