

DESCRIPTION

Servolube oils are non detergent, stationary diesel engine oils, recommended for lubrication of slow and medium speed stationary diesel engines where operating conditions do not require a detergent oil. These oils are also found to give satisfactory performance in the lubrication of reciprocating air compressor. These oils are formulated with selected high quality base stock and multifunctional ashless additive to provide deposit free service.

APPLICATION

Servolube oils are recommended as diesel engine oil for slow and medium speed stationary diesel engines. These oils are also recommended for lubrication of reciprocating air compressors.

PERFORMANCE BENEFITS

- Provide excellent resistance to oxidation, thus permitting extended oil drain intervals
- Minimise carbon deposits on the valve plates.
- Enable trouble free starting at low temperatures
- Provide effective protection against rust and corrosion during routine shut down
- Reduce maintenance cost, due to minimum carbonization.

CHARACTERISTICS

| ISO VG | 68 | 100 | 150 | 220 |
|---------------------------------|-------------|--------|---------|-----------|
| Colour, Max | 5.0 | 6.0 | 7.0 | 8.0 |
| Kinematic Viscosity, cSt @ 40°C | 64.7 – 71.3 | 96-104 | 147-153 | 212 – 228 |
| Viscosity Index, Min, | 90 | 90 | 90 | 90 |
| Flash Point (COC), °C Min | 210 | 216 | 224 | 228 |
| Pour Point, °C Max | (-) 6 | (-) 6 | (-) 6 | (-) 3 |

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20