

PRODUCT DATA SHEET

SERVO SUPER SYNTH 5W-50



DESCRIPTION

Servo Super Synth 5W-50 oil is a full synthetic engine oil that can be used in high performance turbo charged and super charged fuel injected engines. This oil is formulated with synthetic base stock fortified with advanced additive system to provide high performance standard stipulated for gasoline as well as diesel engines. This oil is also used in certain compressor applications.

APPLICATION

Servo Super Synth 5W-50 is suitable for use in high performance turbo charged, super charged petrol and diesel engines fitted in passenger cars, SUV.

PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency.
- ☛ Excellent sludge control and extra wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness and also provide long engine life.
- ☛ Extended drain interval due to reduced oil thickening.

PERFORMANCE STANDARDS

- ☛ Meets API SM/CF
- ☛ Meets MB 229.3

CHARACTERISTICS

SAE GRADE	5W-50
Kin. Viscosity @ 100°C, cSt	17 - 18
Viscosity Index, Min.	150
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 42
TBN, mg KOH/gm	6.8 - 7.8
Sulphated Ash, % wt.	0.86 - 1.02

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20