

# PRODUCT DATA SHEET

## SERVO TOWERGEN 15W-40

**SERVO**<sup>®</sup>

### DESCRIPTION

Servo Towergen 15W-40 is a premium quality, diesel engine oil for generator sets fitted in Telecom Towers. The oil is designed for the most severe performance requirements of continuously operating low and medium capacity diesel generated sets. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

### APPLICATION

Servo Towergen 15W-40 is recommended as engine oil for diesel generated sets fitted in Telecom Towers. This oil is suitable for use in continuously operated low and medium duty diesel generator sets.

### PERFORMANCE BENEFITS

- Reduced engine scuffing & bore polishing.
- High engine cleanliness.
- Maximum protections from wear and deposits.
- Improved control of oil consumption.
- Easier cold starting.
- Excellent all weather performance due to improved cold weather properties.

### PERFORMANCE STANDARDS

- API CF-4
- MB 228.1
- EDL 4 of IS: 13656 - 2002

### CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14.0 – 15.0
Viscosity Index, Min.	135
TBN, mg KOH/g	9.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tservices@indianoil.co.in](mailto:tservices@indianoil.co.in) **OR** [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

May-20