# **SERVO SHOCARM**



### **DESCRIPTION**

Servo Shocarm has been developed as an all weather Shock absorber oil meeting the requirement of Armstrong, UK. Servo Shocarm is low pour product containing phosphorous based anti-wear additive for better wear protection.

## **APPLICATION**

Servo Shocarm is meeting the specifications as Shock absorber for Front Forks shock assembly motorcycles as well as for Rear Shock Absorbers depending upon specification requirements.

### PERFORMANCE BENEFITS

- Increases the life of shock absorber
- Excellent seal compatibility
- Excellent damping effect
- Excellent oxidation stability property
- Excellent high low and temperature performance
- Excellent wear protection
- Excellent low temperature characteristics

# PERFORMANCE STANDARDS

Servo Shocarm is recommended for Shock absorbers of M/s. Hydraulics Ltd.

### **CHARACTERISTICS**

| GRADE                          | Servo Shocarm |
|--------------------------------|---------------|
| Kinematic Viscosity cSt @ 40°C | 12.5 - 14     |
| Density @ 15 Deg C             | 0.8760        |
| Pour Point, °C, Max            | (-) 45        |
| Flash Point, COC, °C, Min      | 150           |

### **HEALTH & SAFETY**

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

May-20

E-Mail: servotechserv@indianoil.in OR servots@indianoil.in