

DESCRIPTION

Servo NG oils are low ash gas engine oil, formulated from high quality mineral base oil and balanced additive system to provide excellent thermal stability and resistance to oxidation and nitration.

APPLICATION

Servo NG oils are recommended for Stationary engines operating on natural gas, CNG, etc.

PERFORMANCE BENEFITS

- High thermal and oxidation stability to reduce oil consumption.
- Reserve TBN neutralizes acids and nitrates to reduce deposits.
- Excellent anti wear properties to control bearing and piston linear wear.
- Effective detergency / dispensing keeps engine clean.

CHARACTERISTICS

SAE GRADE	40	15W-40
Kinematic Viscosity cSt @ 100°C	13.0 – 15.0	14.0 – 15.5
Viscosity Index, Min.	95	130
Flash point (COC), °C Min.	220	200
Pour Point, °C Max.	(-) 6	(-) 24
TBN mg KOH/gm	5 - 5.5	5 - 5.5
S. Ash, % Wt., Max	0.4 - 0.5	0.4 - 0.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20