

PRODUCT DATA SHEET

SERVO 4T ZOOM M2



DESCRIPTION

Servo 4T Zoom M2 is long life high performance engine oil for 4 stroke motorcycles, specially formulated for Mahindra 2 wheelers.

APPLICATION

Servo 4T Zoom is recommended for new generation 4 stroke motorcycles such as CENTURO of Mahindra 2 wheelers for a drain interval of 10000 kms.

PERFORMANCE BENEFITS

- ☞ Maximum power output.
- ☞ Superior performance in terms of oxidation stability.
- ☞ Excellent wear protection at high temperatures and severe operating conditions.
- ☞ Outstanding overall engine cleanliness.
- ☞ Enhanced engine & gear life.
- ☞ Higher fuel efficiency.
- ☞ Potential oil drain period of 10000 kms.

PERFORMANCE STANDARDS

- ☞ JASO T 903 : API SL / JASO MA 2

APPROVALS

- ☞ Mahindra 2 wheelers for its CENTURO Motorcycles for drain interval of 10000 kms.

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min.	120
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN, mg KOH/gm	5.8 – 7.0
Sulphated Ash , % wt	0.72 – 0.88

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20