

PRODUCT DATA SHEET

SERVO GEAR HP 80W-90 (T)



DESCRIPTION

Servo Gear HP 80W-90 (T) oil is an extreme pressure hypoid gear oil. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure, anti wear characteristics.

APPLICATION

Servo Gear HP 80W-90(T) oil is recommended for HCV, LCV transmissions of constant synchromesh type gear boxes.

PERFORMANCE BENEFITS

- Satisfy the lubrication requirements of a wide variety of gears.
- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability.
- Provide good protection against corrosion.
- It is expected to give fuel economy.

PERFORMANCE STANDARDS

Servo Gear HP 80W-90 (T) oil meets:

- API Service GL 4
- IS: 1118-1992
- MAN 341 requirements

CHARACTERISTICS

SAE GRADE	80W-90 (T)
Kinematic Viscosity cSt @ 100°C	14 – 15.5
Viscosity Index, Min.	85
Flash point (COC), °C Min.	160
Pour Point, °C Max.	(-) 27

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20