

PRODUCT DATA SHEET

SERVO 4T ZOOM



DESCRIPTION

Servo 4T Zoom is high performance engine oil for 4 stroke 2/3 wheelers. This oil is a high viscosity index, 4 stroke engine oil.

APPLICATION

Servo 4T Zoom is recommended for new generation 4 stroke motorcycles, scooters and auto rickshaws.

PERFORMANCE BENEFITS

- ☞ Maximum power output.
- ☞ Superior performance in terms of oxidation stability.
- ☞ Excellent wear protection at high temperatures and severe operating conditions.
- ☞ Outstanding overall engine cleanliness.
- ☞ Enhanced engine & gear life.
- ☞ Higher fuel efficiency.
- ☞ Potential oil drain period of more than 5000 Kms.

PERFORMANCE STANDARDS

- ☞ JASO T 903 : API SL / JASO MA 2
- ☞ Meeting API SM specification of Valve Train Wear (VTW).

CHARACTERISTICS

SAE GRADE	10W-30	20W-40	20W-50
Kin. Viscosity @ 100°C, cSt	10 – 12	13.5 – 15.5	17.5 – 19.5
Viscosity Index, Min.	130	110	120
Flash Point, COC, °C, Min	190	200	200
Pour Point, °C, Max	(-) 27	(-) 21	(-) 21
TBN, mg KOH/gm	6.8 – 8.2	6.8 – 8.2	6.8 – 8.2
Sulphated Ash , % wt	0.95 – 1.2	0.95 -1.2	0.95 – 1.2

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20