PRODUCT DATA SHEET

IndianOil **SERVO**®

SERVO SKODA GENUINE OIL XHD

DESCRIPTION

Servo Skoda Genuine Oil XHD is manufactured from carefully selected and highly refined, high viscosity index base stocks. The oil contains appropriate dosages of detergent-dispersant and antioxidant additives to meet the International Performance Standards. The product has capability to ensure trouble free and extended engine life.

APPLICATION

Servo Skoda Genuine Oil XHD is recommended for all CKD (SKODA) Diesel Generating Sets manufactured by M/s CKD HRADEC KRALOVE A.S. Czech Republic and operating on heavier Residual fuels.

PERFORMANCE BENEFITS

- Ensures the long life & smooth performance.
- With excellent detergent / dispersant properties ensure clean crankcase, pistons and valves and prevent ring sticking.
- Effectively combats the deleterious products of combustion associated with high sulphur fuels, thus minimising deposits and wear.
- With excellent engine protection, reducing down time, maintenance and operating cost.
- Minimise deposits resulting from high output, low speed and low temperature operations.

PERFORMANCE STANDARDS

Servo Skoda Genuine Oil XHD meets the following specifications:
- API CD
- US Military MIL-L- 2104 C

M/s CKD Hradec Kralove A.S. Czech Republic the manufacturer of CKD (SKODA) Diesel Generating Sets has approved the use of Servo Skoda Genuine Oil XHD for all CKD (SKODA) DG Sets operating on heavier Residual fuel.

CHARACTERISTICS

SAE GRADE	40
Kinematic Viscosity, cSt @ 100°C	14.2 – 15.5
Viscosity Index, Min.	90
TBN, mg KOH/g	40
Flash Point, (COC)°C, Min.	210
Pour Point °C, Max.	(-) 12

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

May-20