

PRODUCT DATA SHEET

SERVO AUTO RICKSHAW OIL



DESCRIPTION

Servo Auto Rickshaw Oil is blended from highly refined base stocks and balanced additive package containing shear stable VI improver, metallic detergent dispersant and anti-oxidant. These oils are formulated to meet lubrication requirements of both gasoline and diesel engines.

APPLICATION

Servo Auto Rickshaw Oil is recommended for Auto rickshaws running on Petrol and Diesel and encountering continuous start-stop operation. Suitable for all seasons.

PERFORMANCE BENEFITS

- ☞ Enable easy low temperature starting
- ☞ Minimise fuel and oil consumption
- ☞ Give longer battery life
- ☞ Provide maximum protection to engine parts against rust and corrosion
- ☞ Give good high and low temperature performance in the engine
- ☞ Minimise wear of engine parts
- ☞ Ensure system cleanliness by holding contaminants in finely dispersed state

PERFORMANCE STANDARDS

Meets the following specifications:

E-PL 1/E-DL 1 of IS:13656-2002
API SC/CC

CHARACTERISTICS

SAE GRADE	20W-40
Kinematic Viscosity cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	110
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN, mg, KOH/gm	4.5-6.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20