

PRODUCT DATA SHEET

SERVOCUT 353 HYU



DESCRIPTION

Servocut 353 HYU is a sulphur-chlorinated type neat cutting oil. Its selected additives impart marked antiweld properties, which helps machining of intricate shapes with high precision. It has excellent cooling and quick swarf removal characteristics.

APPLICATION

Servocut 353 HYU is recommended for deep hole boring and deep hole drilling of ferrous and ferrous alloys. It gives excellent finish, because of balanced combination of fat, chlorine and active sulphur, under continuous and long work cycle. It is also suitable for certain honing operations. This product is not recommended for machining of non-ferrous metals.

PERFORMANCE BENEFITS

- ☞ Caters for more arduous machining of tough ferrous and ferrous alloys.
- ☞ Gives high precision on long work cycle operations.
- ☞ Provides effective flushing of fine swarf.
- ☞ Ensures faster cooling of tool and work piece.
- ☞ Has minimum rust forming tendency when use in high pressure coolant feed systems.
- ☞ Has minimum misting tendency when used in high pressure coolant feed systems.
- ☞ Assists in achieving high rate of production.
- ☞ Has low sludging tendency to give optimum filter life.
- ☞ Helps achieve longer tool life.

CHARACTERISTICS

	SERVOCUT 353 HYU
Kinematic Viscosity, cSt @ 40°C	18 – 21
Flash Point (COC), °C Min.	160
Pour Point, °C Max.	0
Copper strip corrosion @ 100°C, 3 Hrs, Min.	4

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20