



DESCRIPTION

Servo Premium CG-4 15W-40 is API certified, commercial multipurpose heavy duty diesel engine oil. The oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines for the road transport fleet application and also off highway operations. It assures outstanding protection against high temperature engine deposits, oil thickening degradation, oil and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

PERFORMANCE BENEFITS

- Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Catalytic Converter compatible.

APPLICATION

Servo Premium CG-4 15W-40 is recommended for new generation commercial diesel vehicles of both American and European design such as Caterpillar and Cummins operating on low sulphur fuels.

PERFORMANCE STANDARDS

- API CG4
- MB 228.3
- * MACK EO-M
- MAN 271
- **VOLVO VDS-2**
- Cummins CES 20071 & 20072
- ACEA E3-96 Issue 2
- * ACEA B3-98
- **ACEA A3-98**

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	135
TBN, mg KOH/g	10.0 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24
Sulphated Ash % wt	1.2 – 1.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tservices@indianoil.co.in OR tech services@indianoil.co.in

May-20