

DESCRIPTION

Servo Gas Engine Oil is high performance engine oil for light vehicles operating on Gas. This oil is blended from high viscosity index base stocks and contains additives to meet the stated performance standards.

APPLICATION

Servo Gas Engine Oil is recommended for cars, jeeps, vans etc. operating on Gas. This oil is also suitable for 4 stroke three wheelers operating on Gas.

PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability.
- ☛ Excellent wear protection at high temperatures and severe operating conditions.
- ☛ Long engine life.
- ☛ Catalytic Converter Compatible.

PERFORMANCE STANDARDS

- ☛ API SF/CD
- ☛ IS 13656 –2002 EPL2/EDL2 , SAE 20W 50

CHARACTERISTICS

SAE GRADE	20W-50
Kin. Viscosity @ 100°C, cSt	17.5 – 19.5
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN mg KOH/gm	5.0 – 7.0
Sulphated Ash , % wt	0.6 – 7.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20